

Safety Data Sheet

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	0165B5NL		
	Product Name:	BITUMASTIC 300 M PART B	Revision Date:	05/30/2015
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.	Supercedes Date:	29/05/2015
1.3	Details of the supplier of the safety	v data sheet		
	Manufacturer:	Carboline Company 2150 Schuetz Road St. Louis, MO USA 63146 Regulatory / Technical Informatio Contact Carboline Technical Serv 1-800-848-4645		
	Datasheet Produced by:	Schlereth, Ken - ehs@stoncor.co	m	
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Ins CHEMTREC +1 703 5273887 (Ou HEALTH - Pittsburgh Poison Con	utside US)	

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Eye Irritation, category 2 STOT, single exposure, category 3, RTI Skin Irritation, category 2 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word Warning

Named Chemicals on Label

EPOXY RESIN

GHS HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.
GHS PRECAUTION PHRASES		
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in

+340	IF INHALED: Remove victim to fresh air and keep at rest in
	a position comfortable for breathing.
+251+220	IE IN EVES: Dinco coutiously with water for coveral minutes

P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so.
	Continue rinsing.
P332+313	If skin irritation occurs: Get medical advice/attention.
D222+212	If skin irritation or rash occurs: Get medical advice/attention

P333+313If skin irritation or rash occurs: Get medical advice/attention.P391Collect spillage.

2.3 Other hazards

Not applicable

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients 3.1 Substances Hazardous Ingredients Kasardous Ingredients CAS-No. Chemical Name % 25068-38-6 EPOXY RESIN 75-100 CAS-No. GHS Symbols M-Factors

CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
25068-38-6	GHS07-GHS09	H315-317-319-335-411	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

May cause sensitization by skin contact. Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Evacuate personnel to safe areas. The product is not flammable. Use NIOSH approved respiratory protection. Use water spray to cool unopened containers.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Ensure adequate ventilation.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Avoid breathing vapors, mist

or gas.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks.

STORAGE CONDITIONS: Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

Name	%	ACGIH TLV-	ACGIH TLV-	<u>OSHA PEL-</u>	OSHA PEL-	OEL Note
		<u>TWA</u>	<u>STEL</u>	<u>TWA</u>	<u>CEILING</u>	
EPOXY RESIN	75-100	N/E	N/E	N/E	N/E	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious glovesRequest information on glove permeation properties from the glove supplier.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. Lightweight protective clothing

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	s Viscous Clear To Amber
	Physical State	Liquid
	Odor	Mild Odor
	Odor threshold	
	рН	N/D
	Melting point / freezing point (°C)	N/D
	Boiling point/range (°C)	Not determined
	Flash Point, (°C)	254
	Evaporation rate	

Flammability (solid, gas)

Upper/lower flammability or explosive limits	Not determined
Vapour Pressure, mmHg	N/D
Vapour density	
Relative density	
Solubility in / Miscibility with water	N/D
Partition coefficient: n-octanol/water	
Auto-ignition temperature (°C)	
Decomposition temperature (°C)	
Viscosity	Unknown
Explosive properties	
Oxidising properties	
Other information	
VOC Content g/l:	222
Specific Gravity (g/cm3)	1.16

10. Stability and Reactivity

10.1 Reactivity

9.2

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

Product:	0165B5NL

•••			
11.1	.1 Information on toxicological effects		
	Acute Toxicity:		
	Oral LD50:	N/D	
	Inhalation LC50:	N/D	
	Irritation:	Unknown	
	Corrosivity:	Unknown	
	Sensitization:	Unknown	
	Repeated dose toxicity:	Unknown	
	Carcinogenicity:	Unknown	
	Mutagenicity:	Unknown	
	Toxicity for reproduction:	Unknown	

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
25068-38-6	EPOXY RESIN	11400 mg/kg, rat, oral	23000 mg/kg, dermal, rabbit	>20 mL/kg skin, sensitizer

Additional Information:

May cause sensitization by skin contact. Irritating to eyes and skin. May be harmful if swallowed.

12.	Ecological Information	
12.1	Toxicity:	
	EC50 48hr (Daphnia):	Unknown
	IC50 72hr (Algae):	Unknown
	LC50 96hr (fish):	Unknown
12.2	Persistence and degradability:	Unknown
12.3	Bioaccumulative potential:	Unknown
12.4	Mobility in soil:	Unknown
12.5	Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII

12.6 Other adverse effects:

Unknown

CAS-No.	Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	LC50 96hr
25068-38-6	EPOXY RESIN	2.1 mg/l (daphnia)	11 mg/l (algae)	1.3 mg/l (fish)

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1	UN number	None
14.2	UN proper shipping name	Not Regulated
	Technical name	N/A
14.3	Transport hazard class(es)	None
	Subsidiary shipping hazard	N/A
14.4	Packing group	N/A
14.5	Environmental hazards	Marine Pollutant: Yes (Epoxy Resin)
14.6	Special precautions for user	Unknown
	EmS-No.:	Unknown
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Unknown

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category: EPA VOC Content Limit (g/l): Product VOC Content (g/l) Thinning Recommendations: Application Recommendations:

May be harmful if swallowed.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

California Proposition 65:

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product. Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

* Canadian DSL:

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319Causes serious eye irritation.H335May cause respiratory irritation.H411Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

No Information