

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name

: KOLD-FLO® Pourable Crack Filler

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## 1.3. Details of the supplier of the safety data sheet

Unique Paving Material Corporation 3993 East 93rd Street Clevleand, 44106 - United States of America T (216) 341-7711 http://www.uniquepavingmaterials.com/

1.4. Emergency telephone number

Emergency number

: (800) 424-9300

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GHS-US classification**

Skin Irrit. 2 H315 Eye Irrit. 2A H319 Carc. 1B H350 Full text of H-phrases: see section 16

## 2.2. Label elements

## GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H315 - Causes skin irritation H319 - Causes serious eye irritation H350 - May cause cancer
Precautionary statements (GHS-US)	<ul> <li>P201 - Obtain special instructions before use</li> <li>P202 - Do not handle until all safety precautions have been read and understood</li> <li>P264 - Wash hands thoroughly after handling</li> <li>P280 - Wear personal protective equipment</li> <li>P302+P352 - If on skin: Wash with plenty of water</li> <li>P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing</li> </ul>

P308+P313 - If exposed or concerned: Get medical advice/attention P321 - Specific treatment (see first aid measures on this label) P332+P313 - If skin irritation occurs: Get medical advice/attention P337+P313 - If eye irritation persists: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

P501 - Dispose of contents/container to meet all regulations

## 2.3. Other hazards

No additional information available

## 2.4. Unknown acute toxicity (GHS US)

10 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

15 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

5 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

P405 - Store locked up

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## **SECTION 3: Composition/Information on ingredients**

## 3.1. Substance

## Not applicable

## 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Petroleum Asphalt Base	(CAS No) 8052-42-4	44.775 - 54.945	Carc. 1B, H350
Filler Clay	(CAS No) Trade Secret	13 - 20	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
POTASSIUM HYDROXIDE	(CAS No) 1310-58-3	<= 0 .08	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314

Full text of H-phrases: see section 16

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

4.1. Description of first aid measures		
First-aid measures general		er give anything by mouth to an unconscious person. If you feel unwell, seek medical e (show the label where possible).
First-aid measures after inhalation	keep	oxygen or artificial respiration if necessary. Call a doctor. Remove victim to fresh air and at rest in a position comfortable for breathing. Immediately call a poison center or pr/physician.
First-aid measures after skin contact		ove/Take off immediately all contaminated clothing. Rinse skin with water/shower. ediately call a poison center or doctor/physician.
First-aid measures after eye contact		e cautiously with water for several minutes. Remove contact lenses, if present and easy to continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	with	BE FATAL IF SWALLOWED. Swallowing the liquid may cause aspiration into the lungs the risk of chemical pneumonitis. Rinse mouth. Do NOT induce vomiting. Immediately call son center or doctor/physician.
4.2. Most important symptoms and effe	s, both	acute and delayed
Symptoms/injuries	: Caus	ses serious eye irratation.
Symptoms/injuries after inhalation		ing this product can result in respiratory tract irritation, leading to mild to severe irritation of ose, throat and lungs. Shortness of breath.
Symptoms/injuries after ingestion	: Vom	iting: prevent asphyxia/aspiration pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## **SECTION 5: Firefighting measures**

5.1. Extinguishing media		
Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.	
Unsuitable extinguishing media	: Do not use a heavy water stream.	
5.2. Special hazards arising from the su	ubstance or mixture	
Reactivity	: Stable under normal conditions. Corrosive vapors.	
5.3. Advice for firefighters		
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.	
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.	
Special protective equipment for fire fighters	: Full face piece respirator.	
SECTION 6: Accidental release measures		
6.1. Personal precautions, protective ed	quipment and emergency procedures	
General measures	: Never use a welding or cutting torch on or near drums of this material (even empty drums) because the material can ignite explosively.	
6.1.1. For non-emergency personnel		
Protective equipment	: Wear personal protective equipment.	
Emergency procedures	: Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
Protective equipment	: Equip cleanup crew with proper protection.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: Ventilate area.

## 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

For containment	:	Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up		Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

## 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe fumes. Avoid contact during pregnancy/while nursing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Hygiene measures	: Wash hands thoroughly after handling.
7.2. Conditions for safe storage, including	g any incompatibilities
Technical measures	: Do not store these material for more than six months before using. Empty containers may contain enough residue to emit vapors or to be combustible. Dispose of used containers according to local, state and federal requirements. Protect from freezing. Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from: Keep container closed when not in use.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
7.3. Specific end use(s)	

No additional information available

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

KOLD-FLO® Pour	able Crack Filler			
ACGIH	Not applicable	Not applicable		
OSHA	Not applicable	Not applicable		
Petroleum Asphalt Base (8052-42-4)				
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5		
OSHA	OSHA PEL (Ceiling) (ppm)	OSHA PEL (Ceiling) (ppm) 5 ppm as fumes		
Filler Clay (Trade	Secret)			
ACGIH	Not applicable			
OSHA	Remark (OSHA)	Remark (OSHA) 15 mg/m3 total dust, 5mg/m3 Respirable Dust		

POTASSIUM HYDROXIDE (1310-58-3)	
ACGIH	Not applicable
OSHA	Not applicable

## 8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection Eye protection Skin and body protection	<ul> <li>Wear protective gloves.</li> <li>Chemical goggles or face shield.</li> <li>Provide readily accessible eye wash stations and safety showers. Wear suitable protective clothing.</li> </ul>

Safety Data Sheet

59 / Manday March 26, 2012 / Dulas and Degulations

Respiratory protection	: Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.
SECTION 9: Physical and chemica	Il properties
9.1. Information on basic physical and	d chemical properties
Physical state	: Liquid
Appearance	: Dark, Viscous Liquid.
Color	: Black brown Dark Gray
Odor	: characteristic Tar, Petroleum
Odor threshold	: No data available
рН	: 11.3 - 11.8
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 °F
Flash point	: > 300 °F Cleveland Tag Open Cup Method
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	<ul> <li>Water: Solubility in water of component(s) of the mixture :</li> <li>•: 0.4 % •: • POTASSIUM HYDROXIDE:</li> </ul>

**SECTION 10: Stability and reactivity** 

Other information No additional information available

#### Reactivity 10.1.

Log Pow

Log Kow

Viscosity, kinematic Viscosity, dynamic

Explosive properties

Oxidizing properties

Explosion limits

9.2.

Stable under normal conditions. Corrosive vapors.

#### 10.2. **Chemical stability**

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Avoid contact with strong acids, oxidizing agents and petroleum solvents and soaps to preserve the quality of this material. Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates: Corrosive vapors.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity

: Not classified

No data available

: No data available : No data available

: No data available

: No data available

: No data available : No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum Asphalt Base (8052-42-4)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	
LC50 inhalation rat (mg/l)	> 94.4 ml/m <sup>3</sup>	
Filler Clay (Trade Secret)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat	> 5000 mg/kg	
POTASSIUM HYDROXIDE (1310-58-3)		
LD50 oral rat	1.23 g/kg	
ATE US (oral)	1230.000 mg/kg body weight	
Skin corrosion/irritation	: Causes skin irritation.	
	pH: 11.3 - 11.8	
Serious eye damage/irritation	: Causes serious eye irritation.	
	pH: 11.3 - 11.8	
Respiratory or skin sensitization	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: May cause cancer.	
Petroleum Asphalt Base (8052-42-4)		
IARC group	2A - Probably carcinogenic to humans, 2B - Possibly carcinogenic to humans	
Reproductive toxicity	: Not classified	
Specific target organ toxicity (single exposure)	: Not classified	
Specific target organ toxicity (repeated exposure)	: Not classified	
Aspiration hazard	: Not classified	
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.	
Symptoms/injuries after inhalation	: Inhaling this product can result in respiratory tract irritation, leading to mild to severe irritation of the nose, throat and lungs. Shortness of breath.	
Symptoms/injuries after ingestion	: Vomiting: prevent asphyxia/aspiration pneumonia.	

## **SECTION 12: Ecological information**

12.1. Toxicity

No additional information available

## 12.2. Persistence and degradability

KOLD-FLO® Pourable Crack Filler	
Persistence and degradability	Not established.
Petroleum Asphalt Base (8052-42-4)	
Persistence and degradability	Not established.
POTASSIUM HYDROXIDE (1310-58-3	
Persistence and degradability	Not established.
2.3. Bioaccumulative potential	
KOLD-FLO® Pourable Crack Filler	
Bioaccumulative potential	Not established.
Petroleum Asphalt Base (8052-42-4)	
Bioaccumulative potential	Not established.
Bioaccumulative potential POTASSIUM HYDROXIDE (1310-58-3	

## 12.4. Mobility in soil

No additional information available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects				
Effect on ozone layer				
Effect on the global warming	: No known ecological damage caused by this product.			
Other information	: Avoid release to the environment.			
SECTION 13: Disposal considerations				
13.1. Waste treatment methods				
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to meet all regulations			
Ecology - waste materials	: Avoid release to the environment.			
SECTION 14: Transport information				
In accordance with DOT				
Not Evaluated				
Additional information				
Other information	: No supplementary information available.			
ADR				
Not Evaluated				
Transport by sea				
Not Evaluated				
Air transport				
Not Evaluated				
SECTION 15: Regulatory information				
15.1. US Federal regulations				
Petroleum Asphalt Base (8052-42-4)				
Listed on the United States TSCA (Taxis Substances Control Act) inventory				

# Potroleum Asprint Base (dob 1/2 4) Listed on the United States TSCA (Toxic Substances Control Act) inventory POTASSIUM HYDROXIDE (1310-58-3) Listed on the United States TSCA (Toxic Substances Control Act) inventory Not subject to reporting requirements of the United States SARA Section 313 RQ (Reportable quantity, section 304 of EPA's List of Lists)

## 15.2. International regulations

### CANADA

No additional information available

## **EU-Regulations**

No additional information available

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

## Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

## 15.2.2. National regulations

## 15.3. US State regulations

## Petroleum Asphalt Base (8052-42-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## POTASSIUM HYDROXIDE (1310-58-3)

U.S New Jersey - Right to Know Hazardous Substance List
U.S Pennsylvania - RTK (Right to Know) List

## **SECTION 16: Other information**

Other information

: None.

## Full text of H-phrases:

 Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
 Carc. 1B	Carcinogenicity Category 1B
 Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
 Skin Corr. 1A	Skin corrosion/irritation Category 1A
 Skin Irrit. 2	Skin corrosion/irritation Category 2
 H302	Harmful if swallowed
 H315	Causes skin irritation
 H319	Causes serious eye irritation
 H350	May cause cancer
	-

## GHS US SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product