

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	CITRISTRIP Low VOC Adhesive Remover	
<b>Company Name:</b>	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	<b>Phone Number:</b> (901)775-0100
<b>Web site address:</b>	www.wmbarr.com	
<b>Emergency Contact Information:</b>	3E 24 Hour Emergency Contact W.M. Barr Customer Service	(800)451-8346 (800)398-3892
<b>Intended Use:</b>	Removal of adhesives, mastics, & contact cement from wood, concrete, metal and masonry.	
<b>Synonyms:</b>	GCAR30398, QCAR30397	
<b>Additional Information</b>	This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.	

## 2. HAZARDS IDENTIFICATION

**Skin Corrosion/Irritation, Category 2**  
**Toxic To Reproduction, Category 1B**  
**Specific Target Organ Toxicity (single exposure), Category 3**



<b>GHS Signal Word:</b>	<b>Danger</b>
<b>GHS Hazard Phrases:</b>	H315: Causes skin irritation. H335: May cause respiratory irritation. H336: May cause drowsiness or dizziness. H360: May damage fertility or the unborn child.
<b>GHS Precaution Phrases:</b>	P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P261: Avoid breathing gas/mist/vapors/spray. P264: Wash hands thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves/protective clothing/eye protection/face protection. P281: Use personal protective equipment as required.
<b>GHS Response Phrases:</b>	P302+352: IF ON SKIN: Wash with plenty of soap and water. P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P308+313: IF exposed or concerned: Get medical attention/advice. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P321: Specific treatment see label. P332+313: If skin irritation occurs, get medical advice/attention. P362: Take off contaminated clothing and wash before re-use.
<b>GHS Storage and Disposal Phrases:</b>	P405: Store locked up. P501: Dispose of contents/container according to local, state and federal regulations.

## CITRISTRIP Low VOC Adhesive Remover


Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/23/2015

## Hazard Rating System:

HEALTH	*	1
FLAMMABILITY		1
PHYSICAL		0
PPE		X



NFPA:

## HMIS:

## OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

## Potential Health Effects

## (Acute and Chronic):

## INHALATION ACUTE EXPOSURE EFFECTS:

Vapor harmful. May cause dizziness; headache; burns and severe irritation to the respiratory tract; injuries to mucous membranes; watering of the eyes; weakness; drowsiness; nausea; numbness in fingers, arms, and legs; hot flashes; depression of the central nervous system; spotted vision; fatigue; dilation of pupils; leg and chest pains; eye irritation; giddiness and intoxication; narcosis; anesthesia; confusion; olfactory changes; vomiting; visual disturbances; sleepiness; cough and dyspnea; cold, clammy extremities; diarrhea; irregular or rapid heartbeat; liver and kidney damage; unconsciousness; coma; and death. Severe overexposure may cause irregular or rapid heartbeat, convulsions, unconsciousness, and death. Intentional misuse of this product by deliberately concentrating and inhaling the vapors can be harmful or fatal. This product is a simple asphyxiant.

## SKIN CONTACT ACUTE EXPOSURE EFFECTS:

This product is a skin irritant. Product may be absorbed through the skin. Harmful if absorbed through the skin. May cause itching; irritation; redness; defatting of the skin; drying of the skin; inflammation; discomfort or pain; swelling; dermatitis; and tissue damage. May cause symptoms listed under inhalation and ingestion. May increase the severity of symptoms listed under inhalation.

## EYE CONTACT ACUTE EXPOSURE EFFECTS:

This material is an eye irritant. May cause irritation, burns, swelling, stinging, temporary corneal injury, redness, tearing, blurred vision, conjunctivitis of eyes, and corneal ulcerations of the eye. Vapors may irritate the eyes.

## INGESTION ACUTE EXPOSURE EFFECTS:

May cause nausea; irritation to mouth, throat and stomach; loss of coordination; stupor; changes in white blood cells; drowsiness; rapid heartbeat; low blood pressure; vomiting; gastrointestinal irritation; depression of the central nervous system; narcosis; diarrhea; reddening of face and/or neck; liver, kidney and heart damage; unconsciousness; and death. May produce symptoms listed under inhalation. Liquid aspirated into lungs may cause chemical pneumonitis and systemic effects. Ingestion of significant quantities may result in red blood cell hemolysis.

## CHRONIC EXPOSURE EFFECTS:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged skin contact may cause irritation, redness, swelling and possible tissue destruction. Prolonged or repeated contact may cause dermatitis. Prolonged skin contact may result in absorption of a harmful amount of this material. May cause headaches; conjunctivitis; skin irritation; pancreatic damage; permanent central nervous system changes; gastric disturbances; giddiness; insomnia; decreased response to visual and auditory stimulation; visual impairment or blindness; hallucinations; changes in blood; blood disorders; kidney damage; eye irritation; brain damage; hallucinations; liver damage, and death. May cause additional symptoms listed under inhalation.

**Medical Conditions Generally** Diseases of the blood, skin, eyes, liver, kidneys, lungs, cardiovascular system and

**SAFETY DATA SHEET**  
**CITRISTRIP Low VOC Adhesive Remover**

Page: 3  
Printed: 04/17/2015  
Revision: 04/17/2015  
Supersedes Revision: 03/23/2015

**Aggravated By Exposure:** respiratory system; alcoholism and rhythm disorders of the heart.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
124-17-4	Diethylene glycol monobutyl ether acetate {(a glycol ether)}	70.0 -90.0 %	KJ9275000
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	<10.0 %	UY5790000
929-06-6	2-(2-Aminoethoxy) ethanol	< 3.0 %	KJ6125000

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

### 4. FIRST AID MEASURES

**Emergency and First Aid Procedures:**

**INHALATION:**  
If user experiences breathing difficulty, move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**SKIN CONTACT:**  
Wash with soap and water. Get medical attention if irritation from contact persists.

**EYE CONTACT:**  
Flush eye with water, remove any contact lens, continue flushing for at least 15 minutes, then get medical attention.

**INGESTION:**  
Call your poison control center, hospital emergency room, or physician immediately for instructions.

**Signs and Symptoms Of Exposure:** See Potential Health Effects.

### 5. FIRE FIGHTING MEASURES

**Flash Pt:** > 210.00 F

**Explosive Limits:** LEL: No data. UEL: No data.

**Autoignition Pt:** No data.

**Suitable Extinguishing Media:** Use carbon dioxide, dry powder, or foam.

**Fire Fighting Instructions:** Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

**Flammable Properties and Hazards:** No flash to boil.

Contact of liquid or vapor with flame or hot surfaces will produce toxic gases and a corrosive residue that will cause deterioration of metal.

## 6. ACCIDENTAL RELEASE MEASURES

**Steps To Be Taken In Case Material Is Released Or Spilled:** Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut of ignition sources; keep flares, smoking or flames out of hazard area.

Small Spills: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large Spills: dike far ahead of spill for later disposal.

## 7. HANDLING AND STORAGE

**Precautions To Be Taken in Handling:** Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

**Precautions To Be Taken in Storing:** Store in a cool place in original container and protect from sunlight. Exposure to high temperatures or prolonged exposure to sun may cause can to leak or swell. Once opened, remover should be used within six months or discarded to avoid can deterioration. Do not store near flames or at elevated temperatures.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
124-17-4	Diethylene glycol monobutyl ether acetate {(a glycol ether)}	PEL: 25 ppm STEL: 125 ppm (15 min)	TLV: 50 ppm	No data.
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	PEL: 400 ppm	TLV: 200 ppm STEL: 400 ppm	No data.
929-06-6	2-(2-Aminoethoxy) ethanol	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.

**Respiratory Equipment (Specify Type):** For occasional consumer use - Use with adequate ventilation to prevent a build-up of vapors in confined areas. Open windows or position fans to provide cross ventilation. If a mild to strong odor is noticeable, ventilation is not adequate. For OSHA controlled workplace and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLVs. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved self-contained breathing apparatus. A dust mask does not provide protection against vapors.

**Eye Protection:** Safety glasses, chemical goggles, or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

**Protective Gloves:** Wear impermeable gloves. Gloves contaminated with product should be discarded.

**Other Protective Clothing:** Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.

**Engineering Controls (Ventilation etc.):** Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

**SAFETY DATA SHEET**  
**CITRISTRIP Low VOC Adhesive Remover**

Page: 5  
Printed: 04/17/2015  
Revision: 04/17/2015  
Supersedes Revision: 03/23/2015

**Work/Hygienic/Maintenance Practices:** A source of clean water should be available in the work area for flushing of the eyes and skin.

Wash hands thoroughly after use.  
Do not eat, drink, or smoke in the work area.

Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use.

Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical States:** [ ] Gas [ X ] Liquid [ ] Solid

**Appearance and Odor:** Opaque. Smooth Viscous Liquid

**Melting Point:** No data.

**Boiling Point:** No data.

**Autoignition Pt:** No data.

**Flash Pt:** > 210.00 F

**Explosive Limits:** LEL: No data. UEL: No data.

**Specific Gravity (Water = 1):** No data.

**Density:** 8.2 - 8.4 LB/GL

**Vapor Pressure (vs. Air or mm Hg):** <=

**Vapor Density (vs. Air = 1):** >

**Evaporation Rate:** <

**Solubility in Water:** No data.

**Viscosity:** 2000 - 3000 CPS at 77.0 F

**Percent Volatile:** No data.

**VOC / Volume:** 5.0000 % WT

## 10. STABILITY AND REACTIVITY

**Stability:** Unstable [ ] Stable [ X ]

**Conditions To Avoid - Instability:** No data available.

**Incompatibility - Materials To Avoid:** Incompatible with strong oxidizing agents; strong caustics; and strong alkalis.

**Hazardous Decomposition Or Byproducts:** Decomposition may produce carbon monoxide and carbon dioxide.

**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]

**Conditions To Avoid - Hazardous Reactions:** No data available.

**SAFETY DATA SHEET**  
**CITRISTRIP Low VOC Adhesive Remover**

**11. TOXICOLOGICAL INFORMATION**

**Toxicological Information:** Product not tested as a whole. Refer to section 2 for acute and chronic effects.  
 CAS# 872-50-4:  
**Carcinogenicity/Other Information:** Reproductive Effects:, TDLo, Inhalation, Rat, 116.0 PPM, 6 H, multigenerations.  
 Result:  
 Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).  
 - Drug and Chemical Toxicology., Marcel Dekker, 270 Madison Ave., New York, NY 10016, Vol/p/yr: 18,271, 1995

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Moderate.  
 Result:  
 Blood:Other hemolysis with or without anemia.  
 Blood:Other changes.  
 Biochemical: Metabolism (Intermediary): Other proteins.  
 - Food and Chemical Toxicology., Pergamon Press Inc., Maxwell House, Fairview Park, Elmsford, NY 10523, Vol/p/yr: 26,475, 1988

This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
124-17-4	Diethylene glycol monobutyl ether acetate {(a glycol ether)}	n.a.	n.a.	n.a.	n.a.
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	n.a.	n.a.	n.a.	n.a.
929-06-6	2-(2-Aminoethoxy) ethanol	n.a.	n.a.	n.a.	n.a.

**12. ECOLOGICAL INFORMATION**

**General Ecological Information:** No data available.

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Dispose in accordance with applicable local, state, and federal regulations.

**14. TRANSPORT INFORMATION**

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Paint Related Material, Not Regulated  
**DOT Hazard Class:**  
**UN/NA Number:**

**15. REGULATORY INFORMATION**

**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
124-17-4	Diethylene glycol monobutyl ether acetate {(a glycol ether)}	No	No	Yes-Cat. N230
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	No	No	Yes
929-06-6	2-(2-Aminoethoxy) ethanol	No	No	No

**This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections** [X] Yes [ ] No Acute (immediate) Health Hazard  
 [X] Yes [ ] No Chronic (delayed) Health Hazard  
 [ ] Yes [X] No Fire Hazard

# SAFETY DATA SHEET

## CITRISTRIP Low VOC Adhesive Remover

Page: 7

Printed: 04/17/2015

Revision: 04/17/2015

Supersedes Revision: 03/23/2015

**311/312 as indicated:**       Yes  No    Sudden Release of Pressure Hazard  
                                          Yes  No    Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
124-17-4	Diethylene glycol monobutyl ether acetate {(a glycol ether)}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
872-50-4	N-Methyl-2-pyrrolidone {2-Pyrrolidinone, 1-Methyl-; 1-Methylazacyclopentan-2-one}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test, 12(b); CA PROP.65: Yes
929-06-6	2-(2-Aminoethoxy) ethanol	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 8A, 8A PAIR; CA PROP.65: No

### 16. OTHER INFORMATION

**Revision Date:** 04/17/2015

**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About This Product:** No data available.

**This Product:**

**Company Policy or Disclaimer:** The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.