IDEMITSU

SAFETY DATA SHEET

Product Name:

Pro Honda GN4 MC Oil SAE 10W-40 SJ, 12
x 1 Quart Case

PPE

Transport Symbol

Not regulated

Revision Date: 31-Mar-2015 Revision Number: 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product Name: Pro Honda GN4 MC Oil SAE 10W-40 SJ, 12 x 1 Quart Case

Other means of identification

Product Code: 2208-042

Synonyms Not available

1.2 Recommended use of the chemical and restrictions on use

Recommended Use 4 Stroke Motorcycle Engine Oil

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufactured by Idemitsu Lubricants America Corporation

701 Port Rd.

Jeffersonville, IN. 47130 Telephone: 812-285-8234 Fax: 812-285-8243

Contact Name: Robin Hutchens Email: sds@ilacorp.com

24 Hour Emergency Phone Number Within USA and Canada: 1-800-424-9300

Outside USA and Canada: + 1 703-741-5970 (collect calls

accepted)

Revision Date: 31-Mar-2015

2. HAZARDS IDENTIFICATION

2.1 Classification

This material is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
GHS Physical Hazard Category Number	None

2.2. Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Hazards not otherwise classified (HNOC)

Not applicable

2.3 Other information

Other hazards • Harmful to aquatic life

Avoid release to the environment

Unknown acute toxicity 3.902% of the mixture consists of ingredient(s) of unknown

toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous Components

nazaraous components			
Chemical Name	CAS-No	Weight %	Notes
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	60-70	L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	10-20	L
White mineral oil	8042-47-5	1-5	
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	1-5	L

Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	1-5	L
Calcium long chain alkyl phenate sulphide	68784-26-9	<1	
Phenol, (tetrapropenyl) derivitives	74499-35-7	<1	
distillates (petroleum), hydrotreated light	64742-47-8	<0.1	
Petroleum distillates, solvent dewaxed light paraffinic	64742-56-9	<0.1	L
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	<0.1	L
Phenol,(tetrapropenyl) derivs.,calcium salts	132752-19-3	<0.1	
Phenol, (tetrapropenyl) derivs.	74499-35-7	<0.1	
Ethylene glycol	107-21-1	<0.1	

Non-Hazardous Components

Chemical Name	CAS-No	Weight %
Mineral Base Stock	MIXTURE	90-95

4. FIRST AID MEASURES

4.1 First Aid Measures

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in

attendance.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation

Revision Date: 31-Mar-2015

persists, consult a specialist.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give

oxygen. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty

lean forward to reduce the risk of aspiration. Call a physician or Poison Control Center

immediately.

Protection of First-aidersUse personal protective equipment. Avoid contact with skin, eyes and clothing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties NFPA: Class IIIB Combustible Liquid

5.1 Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment

Unsuitable Extinguishing Media No information available.

5.2 Specific Hazards Arising from the Chemical Keep product and empty container away from heat and sources

of ignition.

Hazardous combustion products:

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and are not limited to, Carbon oxides, Calcium Oxides (CaOx), Hydrogen Sulfide, Nitrogen oxides (NOx), Oxides of Phosphorus, Sulphur oxides, Zinc oxides.

Revision Date: 31-Mar-2015

5.3 Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with the skin and the eyes. Use personal protective equipment. Remove all sources of ignition. Avoid breathing vapors or mists. Ensure adequate ventilation.

6.2 Environmental Precautions

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas. Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 3 for Significant Hazards. See Section 5 for fire fighting information. See Section 4 for First Aid Advice. See Section 8 for Personal Protective Equipment.

6.3 Methods and material for containment and cleaning up

Methods for Clean-up

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceus earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Pick up and transfer to properly labeled containers.

Spill Management

LARGE SPILLS

Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.

WATER SPILLS

Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling

Wear personal protective equipment. Do not breathe vapors or spray mist. Remove and wash contaminated clothing before re-use. Keep away from open flames, hot surfaces and sources of ignition. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Safe Handling Advice

Handle in accordance with good industrial hygiene and safety

practices.

7.2. Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep container tightly closed

in a dry and well-ventilated place.

Revision Date: 31-Mar-2015

Incompatible Materials and/or Coatings

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure Guidelines No exposure limits established

Chemical Name	ACGIH TLV	OSHA PEL	Ontario TWAEV	Mexico (INSQ)	NIOSH IDLH	ILA Internal Exposure Limit
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene						8h TWA: 1 mg/m³ (Inhalable) Toxic effects on blood expected upon exposure
Ethylene glycol	Ceiling: 100 mg/m ³		CEV: 100 mg/m ³	Ceiling: 100 mg/m ³		

Other Exposure Guidelines (If Generated)

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m³		TWA 5 mg/m ³ ST 10 mg/m ³			
Hydrogen sulfide	Ceiling: 20 ppm	TWA: 1 ppm STEL: 5 ppm	5 ppm				

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Eye/face protection Safety glasses equipped with side shields are recommended as minimum protection in

industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or

face-shield.

Skin protection Wear protective gloves/clothing. Use clean protective clothing if splashing or spraying

conditions are present. Protective clothing may include long-sleeve outer garment, apron, or

lab coat. Glove Type: Neoprene, Nitriles.

2208-042 - Pro Honda GN4 MC Oil SAE 10W-40 SJ, 12 x 1 Quart Case

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Revision Date: 31-Mar-2015

provided in accordance with current local regulations.

General Hygiene Considerations When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Yellow Brown / Clear

Physical State Liquid Odor Mild

Odor Threshold No information available

pH Not applicableMelting point / melting range Not applicable

Boiling point / boiling range

No information available

Flash Point > 200 °C / 392 °F COC ASTM D92

Evaporation Rate

Flammability Limit in Air

Explosion Limits

Vapor Pressure

Vapor Density

Density

Solubility

No information available

Solubility

Partition Coefficient (n-octanol/water)

Autoignition Temperature

Decomposing Temperature

No information available
No information available
No information available

Viscosity @ 40C = 92.76 cSt; @ 100C = 13.71 cSt

Other Information

10. STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity The product is chemically stable

10.2 Chemical stability

Chemical Stability Stable under normal conditions.

10.3 Possibility of Hazardous Reactions

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization None under normal processing.

10.4 Conditions to Avoid

Conditions to Avoid Heat, flames and sparks.

10.5 Incompatible Materials

Incompatible Materials Strong oxidizing agents.

10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition may produce hydrogen sulfide and other sulfur-containing gases at temperatures greater than 150F.

Revision Date: 31-Mar-2015

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact May cause slight irritation.

Skin Contact May be harmful in contact with skin.

Ingestion May be harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based 72623-87-1	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	>5.2 mg/L (Rat)4 h
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	> 5000 mg/kg	> 2000 mg/kg	>5 mg/L 4h (Rat)
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	2.18 mg/L (Rat)4 h
White mineral oil 8042-47-5	> 5000 mg/kg (Rat)		>5.2 mg/L (Rat) 4h
Petroleum distillates, solvent-refined heavy paraffinic 64741-88-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	2.18 mg/L (Rat)4 h
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts 68649-42-3	3080 mg/kg (rat)	>2000 mg/kg (rat)	
01154100-5031P	> 5000 mg/kg (Rat)	> 5000 mg/kg(Rabbit)	
Carbonic acid, calcium salt (1:1) 471-34-1	= 6450 mg/kg (Rat)		
distillates (petroleum), hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	5.2 mg/L (Rat) 4 h
Ethylene glycol 107-21-1	4000 - 10200 mg/kg (Rat)	= 10600 mg/kg (Rat) = 9530 µL/kg (Rabbit)	
Poly(dimethylsiloxane) 63148-62-9	> 17 g/kg (Rat)	> 2 g/kg(Rabbit)	
Cyclosilanes, dimethyl- 69430-24-6	> 16 mL/kg(Rat)	> 16 mL/kg(Rabbit)	

11.2 Information on toxicological effects

Symptoms No information available.

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye

irritation

No information available.

Sensitization No information available.

Mutagenic effects No information available.

11.4 Carcinogenicity

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP, IARC, OSHA, or ACGIH.

This product has been demonstrated to contain less than 3% extractables by the IP 346 test and therefore is not carcinogenic or mutagenic. This product shares a CAS number with other substances, "Extracts of steam-refined and air-refined bitumens," that have been classified as possibly carcinogenic to humans (Group 2B) by the International Agency for Research on Cancer (IARC). However, this product is neither steam nor air refined. It is within the IARC class, Bitumens 'not classifiable as to their carcinogenicity to humans

Revision Date: 31-Mar-2015

(Group 3)'.

Chemical Name	ACGIH	IARC	NTP	OSHA	Mexico (INSQ)
Petroleum distillates, hydrotreated heavy paraffinic - 64742-54-7		Group 1			
Petroleum distillates, solvent-refined heavy paraffinic - 64741-88-4		Group 1			
Petroleum distillates, solvent-refined heavy paraffinic - 64741-88-4		Group 1			
Petroleum distillates, hydrotreated heavy paraffinic - 64742-54-7		Group 1			
Petroleum distillates, solvent dewaxed heavy paraffinic - 64742-65-0		Group 1			
Petroleum distillates, solvent dewaxed light paraffinic - 64742-56-9		Group 1			
Petroleum distillates, solvent dewaxed heavy paraffinic - 64742-65-0		Group 1			
Ethylene glycol - 107-21-1					\$ A4 - Not classifiable as a human carcinogen A3*

Legend:

NTP: (National Toxicity Program), ACGIH: (American Conference of Governmental Industrial Hygienists), IARC: (International Agency for Research on Cancer), OSHA: (Occupational Safety & Health Administration)

Reproductive Effects Not available.

STOT - single exposure None known.

STOT - repeated exposure None known.

Chronic Toxicity Avoid repeated exposure.

Aspiration hazard No information available.

11.5 Acute Toxicity

Unknown acute toxicity 3.902% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document.

Product Information (Estimated):

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) 2281 mg/kg
ATEmix (inhalation-dust/mist) 20.3 mg/l

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecotoxicity effects Harmful to aquatic life

Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or

Revision Date: 31-Mar-2015

create an anaerobic environment.

Unknown aquatic toxicity 4.1850000001% of the mixture consists of components(s) of unknown hazards to the

aquatic environment

12.2 Persistence and degradability No information available.

12.3 Bioaccumulation/Accumulation No information available

12.4. Mobility in soil No information available

PBT and vPvB assessment No information available

12.5 Other adverse effects: No information available

Chemical Name	log Pow
White mineral oil 8042-47-5	>6
Ethylene glycol 107-21-1	-1.93

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

To minimize exposure, see Section 8 (Exposure Controls/Personal Protection) of the SDS.

Waste Disposal Method This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated packaging Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

Revision Date: 31-Mar-2015

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are on the inventory or exempt from listing		
DSL	All ingredients are on the inventory or exempt from listing		
NDSL	Not Listed		
EINECS	Does not comply		
ELINCS	Contains an ELINCS substance		
ENCS	Does not comply		
CHINA	All ingredients are on the inventory or exempt from listing		
KECL	All ingredients are on the inventory or exempt from listing		
PICCS	All ingredients are on the inventory or exempt from listing		
AICS	All ingredients are on the inventory or exempt from listing		
NZIoC	All ingredients are on the inventory or exempt from listing		
Mexico (INSQ)	Does not comply		

USA

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS-No	Weight %	HAPS data
Ethylene glycol	107-21-1	<0.1	

State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

Revision Date: 31-Mar-2015

Instability 0

State Right-to-Know

Chemical Name	CAS-No	New Jersey
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	X
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	X

New Jersey Worker and Community Right-to-Know Act:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Lubricating Oil)

Canada

This material has been classified in accordance with the WHMIS 2015 regulation

Chemical Name	CAS-No	Weight %	NPRI
White mineral oil	8042-47-5	<5	Listed
Petroleum distillates, hydrotreated light	64742-47-8	<0.1	Listed
Ethylene glycol	107-21-1	<0.02	Listed


Flammability: 1

Legend

NPRI - National Pollutant Release Inventory

Health: 1

16. OTHER INFORMATION



Prepared By Susie Bibb Revision Date: 31-Mar-2015

Revision Summary: GHS SDS format

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet