

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012. Date of issue: 02/14/2014 Revision date: 02/14/2014 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Mixture

Product name : Sakrete Roof Tile Mortar

Sakrete Glass Block Mortar

Sakrete B-1 Trowel Grade Leveler

Sakrete Sand Mix

Sakrete Stoneworks Mix

Sakrete Stoneworks Stone Veener Mortar Dry Stack Gray Sakrete Stoneworks Stone Veener Mortar Dry Stack Buff

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Various.

Details of the supplier of the safety data sheet

Sakrete of North America 8201 Arrowridge Blvd. 28273 Charlotte, NC - USA T 866-725-7383

Emergency telephone number

: CHEMTREC (800) 424-9300 Emergency number

CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Acute toxicity 4 (Oral) Skin Irritation 2 Serious Eye Damage 1 Skin Sensitization 1 Carcinogenicity 1A

Specific Target Organ Toxicity After Single Exposure 3 Specific Target Organ Toxicity After Repeated Exposure 1

Label elements

GHS-US labelling

Hazard pictograms (GHS-US)







Signal word (GHS-US)

Hazard statements (GHS-US)

: Danger

: Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.

Precautionary statements (GHS-US)

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. If swallowed: Immediately call a poison center/doctor. Rinse mouth. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

02/14/2014 EN (English) Page 1

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

2.3. Other hazards

Other hazards not contributing to the classification

: Not applicable.

2.4. Unknown acute toxicity (GHS-US)

Sakrete B-1 Trowel Grade Leveler: 66 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Sakrete Stoneworks Stone Veener Mortar Dry Stack (Gray): 17 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Sakrete Stoneworks Mix; Sakrete Stoneworks Stone Veener Mortar Dry Stack (Buff): 16 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Sakrete Roof Tile Mortar: 15 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Sakrete Glass Block Mortar; Sakrete Sand Mix: 11 %of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | GHS-US classification |
|--|---------------------|----------------------|--|
| Quartz | (CAS No) 14808-60-7 | 20 - 80 | Acute Tox. 4 (Oral) Carc. 1A STOT RE 1 |
| Plaster of Paris | (CAS No) 26499-65-0 | 30 - 60 ² | Not classified |
| Cement, portland, chemicals | (CAS No) 65997-15-1 | 10 - 30 | Skin Irrit. 2 Eye Dam. 1 Skin Sens. 1 STOT SE 3 |
| Calcium magnesium hydroxide (CaMg(OH)4) | (CAS No) 39445-23-3 | 3 - 7 ¹ | Skin Irrit. 2 Eye Dam. 1 STOT SE 3 |
| Calcium magnesium hydroxide oxide (CaMg(OH)2O) | (CAS No) 58398-71-3 | 3 - 7 ¹ | Skin Irrit. 2 Eye Dam. 1 STOT SE 3 |
| Calcium oxide | (CAS No) 1305-78-8 | 1 - 5 | Skin Irrit. 2 Eye Dam. 1 STOT SE 3 |
| Calcium hydroxide | (CAS No) 1305-62-0 | 1 - 5 ¹ | Eye Dam. 1 Skin Corr. 1B |
| Calcium sulfate | (CAS No) 7778-18-9 | 1 - 5 | Not classified |
| Limestone | (CAS No) 1317-65-3 | 1 - 5 | Not classified |
| Iron oxide (Fe2O3) | (CAS No) 1309-37-1 | 1 - 5 ³ | Not classified |
| Magnesium oxide (MgO) | (CAS No) 1309-48-4 | 1 - 5 ³ | Not classified |
| Magnesium hydroxide | (CAS No) 1309-42-8 | 1 - 5 ¹ | Not classified |

¹ Sakrete Glass Block Mortar

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact

: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

First-aid measures after eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

First-aid measures after ingestion

: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation

: May cause respiratory tract irritation.

Symptoms/injuries after skin contact

: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.

Symptoms/injuries after eye contact

 Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

02/14/2014 EN (English) 2/8

² Sakrete B-1 Trowel Grade Leveler

³ Sakrete Roof Tile Mortar; Sakrete Glass Block Mortar; Sakrete B-1 Trowel Grade Leveler; Sakrete Sand Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Symptoms/injuries after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Treat for surrounding material.

Unsuitable extinguishing media : Not available.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

Firefighting instructions : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and material for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter

waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Vacuum or sweep material and place in a disposal container.

6.3. Reference to other sections

No additional information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not swallow. Avoid contact with skin and eyes. Good housekeeping is important to prevent

accumulation of dust. Avoid generating and breathing dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care.

When using do not eat, drink or smoke.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container

tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water

sprinklers.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Quartz (14808-60-7) | | |
|---------------------|------------------------|--|
| USA ACGIH | ACGIH TWA (mg/m³) | 0.025 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | (30)/(%SiO ₂ + 2) mg/m ³ TWA, total dust (250)/(%SiO ₂ + 5) mppcf TWA, respirable fraction (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction |

| Cement, portland, chemicals (65997-15-1) | | |
|--|------------------------|---------|
| USA ACGIH | ACGIH TWA (mg/m³) | 1 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ |

| Calcium oxide (1305-78-8) | | |
|---------------------------|------------------------|---------|
| USA ACGIH | ACGIH TWA (mg/m³) | 2 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ |

| Calcium hydroxide (1305-62- | 0) | |
|-----------------------------|-------------------|---------|
| USA ACGIH | ACGIH TWA (mg/m³) | 5 mg/m³ |

02/14/2014 EN (English) 3/8

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| Calcium hydroxide (1305-62-0) | | | |
|---------------------------------|-----------------------------------|---|--|
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ | |
| Coloium aulfata (777 | 70.40.0\ | | |
| Calcium sulfate (777 | · | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ | |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ | |
| Limestone (1317-65- | -3) | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ | |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m³ | |
| Iron oxide (Fe2O3) (| 1309-37-1) | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 5 mg/m³ | |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 10 mg/m³ | |
| Magnesium oxide (N | Magnesium oxide (MgO) (1309-48-4) | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ | |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ | |
| Magnesium hydroxide (1309-42-8) | | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ | |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ | |
| Plaster of Paris (264 | Plaster of Paris (26499-65-0) | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ (total); 5 mg/m³ (respirable) | |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³(total); 5 mg/m³ (respirable) | |
| | | - · · · · · · · · · · · · · · · · · · · | |

Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below

recommended exposure limits.

Hand protection : Wear suitable waterproof gloves.

Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and

face protection (face shield).

: Wear suitable waterproof protective clothing. Skin and body protection

Respiratory protection : A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used

under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection

(Z88.2).

Other information Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully

before eating or smoking. Handle according to established industrial hygiene and safety

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state : Solid : Powder. **Appearance** Colour Various. Odour Characteristic. Odour threshold : No data available.

Ηа

: 12 - 13 Relative evaporation rate (butylacetate=1) : No data available. Melting point : No data available. Freezing point : No data available. Boiling point : No data available. Flash point : No data available. Self ignition temperature : No data available. : No data available. Decomposition temperature Flammability (solid, gas) : Not flammable.

02/14/2014 EN (English) 4/8

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

: No data available. Vapour pressure Relative vapour density at 20 °C : No data available. Relative density : No data available. Solubility : No data available. Log Pow : No data available. Log Kow : No data available. : No data available. Viscosity, kinematic Viscosity, dynamic : No data available. Explosive properties : No data available. Oxidising properties : No data available. Explosive limits : No data available.

Other information

VOC content : 0%, Not applicable; 0 wt, Not applicable.

SECTION 10: Stability and reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

Stable under normal storage conditions. Keep dry in storage.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Incompatible materials. Moisture.

Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

Information on toxicological effects

| Acute toxicity | : Harmful if swallowed. |
|-----------------------------------|---|
| | iss Block Mortar; Sakrete B-1 Trowel Grade Leveler; Sakrete Sand Mix; Sakrete Stoneworks Mix; ortar Dry Stack (Gray); Sakrete Stoneworks Stone Veener Mortar Dry Stack (Buff) |
| LD50 oral rat | 563 - 741 mg/kg |
| LD50 dermal rabbit | No data available. |
| LC50 inhalation rat (mg/l) | No data available. |
| Quartz (14808-60-7) | |
| LD50 oral rat | 500 mg/kg |
| Calcium oxide (1305-78-8) | |
| LD50 oral rat | > 2000 mg/kg |
| Calcium hydroxide (1305-62-0) | |
| LD50 oral rat | 7340 mg/kg |
| Calcium sulfate (7778-18-9) | |
| LD50 oral rat | > 3000 mg/kg |
| Limestone (1317-65-3) | |
| LD50 oral rat | 6450 mg/kg |
| Iron oxide (Fe2O3) (1309-37-1) | |
| LD50 oral rat | > 10000 mg/kg |
| Magnesium oxide (MgO) (1309-48-4) | |
| LD50 oral rat | > 5000 mg/kg |
| Magnesium hydroxide (1309-42-8) | |
| LD50 oral rat | 8500 mg/kg |
| | |

02/14/2014 EN (English) 5/8

Safety Data Sheet

| according to the Hazard Com | | |
|-----------------------------|--|--|
| | | |
| | | |

| Skin corrosion/irritation | : | Causes skin irritation. |
|-----------------------------------|---|--------------------------------------|
| Serious eye damage/irritation | : | Causes serious eye damage. |
| Respiratory or skin sensitisation | : | May cause an allergic skin reaction. |

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : May cause cancer.

| Quartz (14808-60-7) | |
|--|---|
| IARC group | 1 |
| National Toxicity Program (NTP) Status | 2 |

| Iron oxide (Fe2O3) (1309-37-1) | |
|--------------------------------|---|
| IARC group | 3 |

Reproductive toxicity : Based on available data, the classification criteria are not met. Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated exposure)

: Causes damage to lungs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)

Aspiration hazard : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation Symptoms/injuries after skin contact : May cause respiratory tract irritation.

: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin

Symptoms/injuries after eye contact

Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries after ingestion

: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

12.2. Persistence and degradability

Sakrete Roof Tile Mortar; Sakrete Glass Block Mortar; Sakrete B-1 Trowel Grade Leveler; Sakrete Sand Mix; Sakrete Stoneworks Mix; Sakrete Stoneworks Stone Veener Mortar Dry Stack (Gray); Sakrete Stoneworks Stone Veener Mortar Dry Stack (Buff)

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Sakrete Roof Tile Mortar; Sakrete Glass Block Mortar; Sakrete B-1 Trowel Grade Leveler; Sakrete Sand Mix; Sakrete Stoneworks Mix; Sakrete Stoneworks Stone Veener Mortar Dry Stack (Gray); Sakrete Stoneworks Stone Veener Mortar Dry Stack (Buff)

Bioaccumulative potential No data available.

12.4. Mobility in soil

Sakrete Roof Tile Mortar; Sakrete Glass Block Mortar; Sakrete B-1 Trowel Grade Leveler; Sakrete Sand Mix; Sakrete Stoneworks Mix; Sakrete Stoneworks Stone Veener Mortar Dry Stack (Gray); Sakrete Stoneworks Stone Veener Mortar Dry Stack (Buff)

Ecology - soil No data available

12.5. Other adverse effects

Other adverse effects : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

02/14/2014 EN (English) 6/8

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cement, portland, chemicals (65997-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium magnesium hydroxide (CaMg(OH)4) (39445-23-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium magnesium hydroxide oxide (CaMg(OH)2O) (58398-71-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium hydroxide (1305-62-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium sulfate (7778-18-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Iron oxide (Fe2O3) (1309-37-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium oxide (MgO) (1309-48-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Magnesium hydroxide (1309-42-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State regulations

Sakrete Roof Tile Mortar; Sakrete Glass Block Mortar; Sakrete B-1 Trowel Grade Leveler; Sakrete Sand Mix; Sakrete Stoneworks Mix; Sakrete Stoneworks Stone Veener Mortar Dry Stack (Gray); Sakrete Stoneworks Stone Veener Mortar Dry Stack (Buff)

State or local regulations

This product contains Crystalline Silica, Quartz and may also contain other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

02/14/2014 EN (English) 7/8

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

| SOURCE AGENCY CARCINOGEN CLASSIFICATIONS: | |
|---|--|
| IARC (I) | International Agency for Research on Cancer. |
| | Carcinogenic to humans; A - Probably carcinogenic to humans; B - Possibly carcinogenic to humans; Not classifiable; 4 - Probably not carcinogenic to humans. |
| NTP (N) | National Toxicology Program. |
| | 1 - Evidence of Carcinogenicity; 2 - Known Human Carcinogens; 3 - Reasonably anticipated to be Human Carcinogen; 4 - Substances delisted from report on Carcinogens; 5 - Twelfth Report - Items under consideration. |

SECTION 16: Other information

Indication of changes : None.
Other information : None.

NFPA health hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention

was given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure

conditions, and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

02/14/2014 EN (English) 8/8